



THOR Tarp
DIV. OF **ODIN** INTERNATIONAL, INC.



ThoroShield 4050 FR Black

Specification & Data Sheet

TEAR-OFF TARPS

SPECIFICATIONS

MANUFACTURED FROM 40 OUNCE PER SQUARE YARD VINYL COATED POLYESTER

TENSILE STRENGTH (WXF) 1,100 LBS X 880 LBS/ 2 INCH
PUNCTURE RESISTANCE 176 LBS (SCREWDRIVER METHOD)
PUNCTURE RESISTANCE 990 LBS (BALL METHOD)

CRISS-CROSS PATTERN SEWING WITH 2" WIDE CARGO WEBBING

BREAK STRENGTH: 12,000 LBS
SAFE WORK LOAD 4,000 LBS

3" DIAMETER X 3/8" STOCK STEEL O RINGS ON ALL WEBBED ENDS

3,000 LB CAPACITY: STRAIGHT PULL METHOD

ALL SEWING WITH 207 POLYESTER, ULTRA VIOLET RESISTANT THREAD WITH CARGO RESTRAINT COMPLIANT STITCH PATTERNS

NOTE: FOR SIZES OVER 10' X 10', A 'PLUS' WEB CONFIGURATION IS SEWN ADJACENT TO THE CRISS CROSS PATTERN.

Disclaimer: DUE TO NORMAL WEAR AND MATERIAL DEGRADATION, NEVER USE THIS PRODUCT ABOVE PERSONNEL OR EQUIPMENT

CORPORATE HQ: P.O. BOX 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM